



FARMING WITH PASSION

6549 SUPER



*T&Cs apply



Heavy Duty

4WD

Transmission

SIDE SHIFT 12F + 12R



PREET 6549 SUPER - 4WD

ENGINE						
Model / Make	<i>PREET</i> 6549					
HP Category	65					
Type	Four Stroke, Natural Aspiration, DI					
No. of Cylinders	4 Cylinder					
Bore / Stroke (mm)	105 / 118					
Rated Engine (RPM)	2200					
Displacement (cc)	4088					
Fuel Pump	Multicylinder, Inline (Bosch)					
Air Cleaner Type	Dry					
Cooling System	Liquid Cooled					
CLUTCH						
Type	Heavy Duty, Dual, Dry Friction Plates & Pads With Diaphragm					
Plate Size	Dia 310 / 340 mm					
TRANSMISSION						
Gear Box	12F+12R, Synchromesh					
ROAD SPEED KM/hr	Forward			Reverse		
Gear	HIGH	MEDIUM	LOW	HIGH	MEDIUM	LOW
1	10.35	3.90	1.54	8.68	3.27	1.29
2	15.33	5.78	2.28	12.86	4.85	1.91
3	22.43	8.46	3.33	18.81	7.09	2.79
4	32.00	11.89	4.68	26.44	9.97	3.93
HYDRAULIC SYSTEM						
Type	2 Lever, ADDC					
Hydraulic Pump	Gear Type					
Linkage	TPL Category - I & II					
Lifting Capacity (kg)	2000					
STEERING						
Type	Hydrostatic, Power Steering					

Note : As per our policy is that of continuous development, specifications may change without any prior notice.
For further details contact your nearest dealer.

PREET TRACTORS PVT. LTD.

Patiala Road, NABHA-147 201 (Pb.) INDIA. Tel.: 01765-220400, 222609
Toll Free : 1800-419-0349 Email: info@preet.co | Visit us at: www.preet.co

Technical Specifications

POWER TAKE OFF	
Type	Live PTO (Optional GPTO and Reverse PTO)
Splines	6 (optional:21)
PTO / Speed	540 (optional:1000)
CAPACITIES (LITRES)	
Fuel Tank	67
Engine Sump	10.8
Cooling System	11.1
Transmission & Hydraulic	35
Steering System	2
ELECTRICAL INSTALLATION	
Battery	12V, 100Ah
Alternator	12V, 42A
Starter Motor	12V, 2.7KW
MIN. TURNING RADIUS	
Without Brakes (m)	4.8
TYRE SIZE	
Front	9.5 -24
Rear	16.9 - 28
Weight, kg	2450
FRONT DRIVE AXLE - CARRARO	
Differential	Limited Slip
Bevel Ratio	1:2.133
Hub Ratio	1:6
Total Ratio	1:12.8
Diff. Oil Capacity (Ltr.)	5.5±0%
Hub Oil Capacity (Ltr.)	0.6±15% Each Side
BRAKES	
Type	Multi Disc Oil Immersed
Overall Dimensions (mm)	
Length	3960
Width	2070
Height upto Exhaust	2390
Wheel Base	2330
Ground Clearance	405
Front Wheel Track	1580 (STD)
Rear Wheel Track	1630 (STD)

Authorised Dealer