Solis

BUILT FOR PERFORMANCE. DESIGNED FOR TOMORROW.

4087 cc
HIGH TORQUE ENGINE

385 Nm
MAXIMUM TORQUE

3,500 kg
OPTIONAL REAR LIFT

80 L/min
HYDRAULIC FLOW

S 95 SHUTTLE XL



High-capacity performance for demanding implements, long working days and tough field conditions.

90 HP Stage V power with high torque, advanced hydraulics and intelligent tractor control.

POWER FOR THE FULL FARMING CYCLE

S95 combines field performance, hydraulic capacity and transport speed for large farms and demanding contractors.



PRIMARY & SECONDARY TILLAGE

High torque, 4WD and draft control support ploughing, cultivation and seedbed preparation.



SEEDING & CROP ESTABLISHMENT

Multiple working speeds and responsive hydraulics support accurate operation with matched implements.



PTO-INTENSIVE OPERATIONS

540 and 540 E RPM PTO speeds support mowing, baling and other powered applications.



HAULAGE & FARM LOGISTICS

A 40 km/h maximum speed and available trailer-brake systems support efficient movement between jobs.

CAPABILITY FOR DEMANDING WORK

Core systems that expand productivity across applications.

1.	12F+12R Synchro Shuttle	2.	Auto 4WD Automatic Traction
3.	80 L/Min Hydraulic Pump Flow	4.	540/540E Rear PTO Speeds
5.	20F+20R Optional Creeper	6.	Lift-O-Matic Fast Linkage Control
7.	2/3 DA Rear Remotes	8.	S-Connect Telematics Ready
9.	Cruise Control	10.	PTO Stabilizer
11.	Electronic hand accelerometer	12.	Engine & Vehicle Speed limiter

PERFORMANCE WITH INTELLIGENT CONTROL



S95 combines heavy-duty mechanical capability with features that reduce operator effort and improve consistency.

90 HP STAGE V ENGINE

4.1 L, 4-cylinder turbo-intercooled engine delivers 385 Nm at a relaxed 1,400 rpm rating.

80 L/MIN HYDRAULICS

High pump flow supports faster implement response and multiple hydraulic functions.

AUTO 4WD

Automatic engagement helps maintain traction while reducing manual intervention.

AUTO PTO & PTO STABILIZER

Automatic engagement and optional speed stabilization support consistent PTO work.

12F+12R SYNCHRO SHUTTLE

Smooth direction changes, 40 km/h transport speed and optional 20F+20R creeper.

UP TO 3,500 KG LIFT

CAT II linkage with mechanical draft control, top-link sensing and Lift-O-Matic.

HYDRAULIC-ASSISTED BRAKES

Powerful braking with lower pedal effort supports operator confidence and control.

S-CONNECT READY

Telematics enables tracking, diagnostics service alerts and fleet-performance insights.

1.	Collision Detection	2.	Driver Behavior Analysis
3.	Theft Deterrent	4.	540/540 E Rear PTO Speeds
5.	Engine Immobilization	6.	Vehicle Diagnostics
7.	SOS Emergency	8.	Geo Fencing
9.	Vehicle Service Alert	10.	Model Management
11.	Vehicle Health Report	12.	Live Parameter Monitoring
13.	Vehicle Analytics Report	13.	Trip Management

SPECIFICATIONS

FEATURES	S95 SHUTTLE XL
ENGINE	
Cylinders / capacity	4 / 4,087 cc
Rated power	67.3 kW / 90 HP
Rated speed / Torque	2200 rpm / 385 Nm
Aspiration	Turbocharged, intercooled
Emissions / after treatment	Stage V / DOC + DPF + SCR
Fuel / DEF tank	110 L / 8.8 L
HYDRAULICS	
Pump flow	56 L/min
Rear lift capacity	3,000 / 3,500 kg optional
Linkage / control	CAT II / mechanical draft
Rear remote	2 DA / 3 DA (Std.)
TRANSMISSION	
Standard gearbox	12F+12R synchro shuttle
Optional Creeper	20F+20R
Speed range	1.72 to 40 km/h
Creeper speed range	0.2 to 40 km/h
ELECTRICAL	
Battery / alternator	130 Ah, 800 CCA / 120 A
PTO	
Rear PTO	540 / 540E
PTO type	Independent
BRAKES & DRIVE	
4WD actuation	Automatic 4WD
Brake actuation	Hydraulic assisted

FEATURES	S95 SHUTTLE XL
DIMENSIONS	
Weight	4,205 kg / 3,890 kg unladen
Wheelbase	2,350 mm
Length / width / height	4,180 / 2,035 / 2,700 mm
Gound clearance	420 mm
Front / rear track	1,670 / 1,500 mm
REAR HITCHES	
Option 1	E mark Swinging Drawbar
Option 2	Semi-Automatic Ladder Hitch
Option 3	Cuna Ladder Hitch
Option 4	Automatic Ladder Hitch



AGRI (Std.)
12.4-24 | 18.4-30
RADIAL (Opt.)
320/70 R24 | 460/85 R30
420/65 R24 | 540/65 R34
280/85 R24 | 420/85 R30
320/70 R24 | 480/70 R30
360/70 R20 | 480/70 R28
360/70 R20 | 420/70 R30
320/70 R20 | 420/70 R28

INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No. 10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)
Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/522221
Fax:+91-01882-522222 | Email: info@solisworld.com | URL: www.solistractors.com