Solis

THE POWER TO DO MORE

3065 cc
HIGH TORQUE ENGINE

290 Nm
MAXIMUM TORQUE

3,000 kg
OPTIONAL REAR LIFT

12F+12R
SYNCHROMESH
SHUTTLE TRANSMISSION

S75 SHUTTLE XL



Built for tillage, crop care, material handling and transport across the farming season.

67 HP Stage V performance with 290 Nm torque, shuttle control and powerful hydraulics.

CAPABILITY ACROSS THE FARMING SEASON

Shuttle control, 4WD traction and flexible hydraulics support demanding work across changing field conditions.



TILLAGE & SEEDBED PREPARATION

High torque and 4WD traction support ploughing, cultivation and rotary implement work.



SOWING & CROP CARE

The 12F+12R gearbox helps match tractor speed to the implement and field conditions.



LOADER & MATERIAL HANDLING

Two auxiliary remotes as standard support loader work and hydraulic attachments.



TRANSPORT & HAULAGE

Oil immersed brakes and 290 Nm torque support controlled movement under load.

STANDARD S70 FEATURES

A complete utility tractor package for productive field and transport work.

1.	12F+12R synchromesh shuttle	2.	Oil immersed brakes
3.	Mechanical differential lock	4.	Mechanical 4WD actuation
5.	Power steering	6.	Double clutch
7.	Two auxiliary remotes	8.	Flat operator platform
9.	Metal hood	10.	Quad projector headlamps
11.	Best in class lift capacity 3000 Kg	12.	USB C-type port

PERFORMANCE FOR DEMANDING WORK



The S75 combines engine torque, shuttle control and hydraulic capacity for efficient implement operation.

67 HP STAGE V ENGINE

A 3,065 cc turbocharged and intercooled engine delivers power at 2,000 rpm.

2,215 MM WHEELBASE

The long wheelbase supports stability during field and transport operations.

405 MM GROUND CLEARANCE

Clearance supports work on uneven ground and challenging field conditions.

45 L/MIN IMPLEMENT FLOW

Quick hydraulic response supports smoother lifting and implement movement.

12F+12R SYNCHRO SHUTTLE

Synchromesh shuttle control supports a wider working range and directional changes.

UP TO 3,000 KG REAR LIFT

Optional hydraulic capacity expands compatibility with heavier implements.

THREE-SPEED REAR PTO

540, 540E rpm
options suit a wider range of PTO implements.

290 NM MAXIMUM TORQUE

Peak torque arrives at 1,500 rpm to support field work and haulage.

SPECIFICATIONS

FEATURES	S 75 SHUTTLE XL
ENGINE	
Engine type	3 Cylinder, Turbocharged Intercooled
Power Category	67 HP
Displacement	3,065 cc
Rated speed	2,000 rpm
Maximum torque	290 Nm @ 1,500 rpm
Air cleaner	Dry type
HYDRAULICS	
Three-point linkage	CAT II
Rear lift capacity	2,500kg I 3,000 kg (Opt.)
Hydraulic flow	24 L/min steering + 45 L/min implement
Auxiliary circuit	2 DA / 3 DA (Opt.)
TRANSMISSION	
Drive / Gear Box	4WD / 12F + 12R Shuttle
Speed range	1.45 to 31.62 km/h
Clutch	Double Clutch
PTO	
Rear / mid PTO	540 / 540E
PTO actuation	Mechanical
DIMENSIONS	
Weight	2,935 kg
Wheelbase	2,215 mm
Length / Width / Height	4,080 / 1,837 / 2,656 mm
Ground Clearance	405 mm

FEATURES	S 75 SHUTTLE XL
BRAKES & STEERING	
Service brakes	Oil immersed
Differential lock	Mechanical
Steering	Power steering
CAPACITIES	
Fuel Tank	65 L
ELECTRICAL	
Battery / alternator	12V-110Ah / 90A
EXHAUST	
Standard / Optional	Updraft / Downdraft

TYRE COMBINATIONS

AGRI
7.5-16 + 14.9-28 | 8.5-24+14.9-28 9.5-24 | 14.9-28
RADIAL
250/85R20 | 340/85R28 320/70R24 | 480/70R28
RADIAL
250/85R20 + 340/85R28 | 320/70R24 + 480/70R28
TURF
300/70R20 + 340/85R28
INDUSTRIAL
12.5-80 + 18.4-24

INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No. 10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)
Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/522221
Fax:+91-01882-522222 | Email: info@solisworld.com | URL: www.solistractors.com