

L60

SPECIFICATION

FEATURES	L60
ENGINE 	
HP Category	60 HP
No. of Cylinder	3
Aspiration	Naturally Aspirated
Cubic Capacity	3530
Rated RPM	2100
Air Cleaner	Dry Type
Max Torque (Nm)	242@1400
Exhaust	Downdraft
TRANSMISSION 	
Drive	4WD
Type	Synchromesh Shuttle
Gearbox	12+12
Front Axle	4WD
SPEED (FORWARD) 	
Maximum Speed (km/hr)	28.11
Minimum Speed (km/hr)	0.5
BRAKES 	
Brakes	Oil Immersed
Type of Actuation	Mechanical
Parking Brake	Latch Type
Differential Lock	Foot Operated
PTO 	
PTO (RPM)	Read – 540, 540E
PTO (Actuation)	Mechanical
STEERING 	
Steering	Power Steering
ELECTRICALS 	
Battery	12V, 110AH
Alternator	12V, 90 Amp
HYDRAULICS 	
3 Point Linkage	Cat 2
Control Type	ADDC

FEATURES	L60
EQRL	Std.
Lifting Capacity (Kg)	2500
Stay Bars	Anchor Chain
Auxiliary Hydraulic Circuit	2DA Std., 3DA (Optional)
Lift Rods	Yes
LPM (Litre per minute)	45
CAPACITY (LITRES ±6%) 	
Fuel Tank	65
TYRE 	
Front	280/70R18
Rear	340/85R28
OVERALL DIMENSIONS 	
Weight (Kg)	2830
Wheel Base (mm)	2160
Total Length (mm)	4075
Total Width (mm)	1715
Height (mm) up to ROPS	2300
Height (mm) up to Driver Seat	1170
Height (mm) up to Fender	1330
Front Track (mm)	1310
Rear Track (mm)	1370
Ground Clearance (mm)	275
Turning Radius (m)	4.5
OPTIONAL FEATURES 	
Trailer Hitch - Option 1	Clevis Hitch
Front Toe Hook	Yes, Available
3 Point Linkage Type	Self Locking Linkage
OPTIONAL TYRES	
Option 1	Front : 280/70R18, Rear : 420/70R24
Option 2	Front : 260/70R16, Rear : 360/70R24
Option 3	Front : 280/70R18, Rear : 360/70R28
Option 4	Front : 280/70R18, Rear : 380/70R28
Option 5	Front : 280/70R18, Rear : 380/85R28