

# SV26

## SPECIFICATION

FEATURES	SV26
<b>MOTOR</b>	
Traction Motor	
Power	17 kw
Rated RPM	2500
<b>BATTERY</b>	
Model	Li-Ion Battery
Rated Capacity	308Ah
Rated Voltage	76.8V
Auxillary Battery	20AH
<b>TRANSMISSION</b>	
Drive	4WD
Clutch	Wet Type Clutch for PTO
Gearbox	Hydrostatic
Front Axle	4WD
Transmission	2-Stage Hydrostatic
<b>SPEED (FORWARD)</b>	
Maximum Speed (Km/Hr)	19.67 @ full flyup 2700 RPM
Minimum Speed (Km/Hr)	2.91 @ 900 ERPM, 8.75 @ 2700 ERPM
<b>BRAKES</b>	
Brakes	Oil Immersed Brakes
Type of Actuation	Single Push Pedal
Parking Brake	Independent
<b>DIFFERENTIAL LOCK</b>	
Differential Lock	Yes, Foot Operated
<b>PTO</b>	
PTO (rpm)	Mid PTO - 2100 RPM, Rear 540
PTO (actuation)	Electrohydraulic
<b>STEERING</b>	
Steering	Power Steering
<b>ELECTRICAL</b>	
Seven Pin Trailer Socket	Standard
<b>HYDRAULICS</b>	
3 Point Linkage	Cat 1-N
Stay Bars	Anchor Chain
Additional Hydraulic Circuit	1 DA

FEATURES	SV26
Hydraulic Lifting Capacity	Std. 600 & Opt. - 750
Lift Rods	Standard
Litre per Minute (LPM)	15.07 @ 2500 RPM
<b>SAFETY SWITCH</b>	
PTO Safety	Standard
Neutral Safety Switch	Standard
<b>TURNING RADIUS</b>	
Without Brakes (m) as per Standard Tyres	3.4
<b>TYRE</b>	
Front	25*8.50-14
Rear	13.6*16
<b>DIMENSION &amp; WEIGHT(+/-5%)</b>	
Weight (Kg)	1365
Wheel Base (mm)	1560
Total Length (mm)	2960
Total Width (mm)	1200
Height (mm) Up to ROPS	2325
Min Ground Clearance (mm)	210
Front Track (mm)	940
Rear Track (mm)	1000
<b>OTHERS</b>	
Front Tow Hook	Standard
Trailer Hitch	E Mar Swinging Bar (Std), Clevis Hitch, Semi Automatic Hitch
ROPS	Yes
<b>TYRES</b>	
<b>RADIAL AGRI</b> Front 6.5/80-12 Rear 280/70 R18	<b>AGRI</b> Front 6x12 Rear 8.30x20
<b>TURF</b> Front 25x8,50-14 Rear 13.60-16	<b>INDUSTRIAL</b> Front 23x8,50-12 Rear 33x15,50-16,5
<b>GALAXY PRO</b> Front 220/55R12 Rear 280/70R16	
Front loader	YES optional

\*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All dimensions are with standard tyres.