Solis

COMPACT BY DESIGN. TOUGH BY NATURE.

25 km/h
MAX SPEED

76.3 Nm
MAXIMUM TORQUE

775 kg
LIFTING CAPACITY

9F+9R
SYNCHRO SHUTTLE



Easy to manoeuvre. Comfortable to operate. Ready for more jobs.

A Stage V compact tractor with shuttle convenience, strong hydraulics and year-round versatility.

ONE COMPACT TRACTOR. MORE POSSIBILITIES.

Compact dimensions, shuttle control and flexible PTO and hydraulics make the S30 useful across the working year



ORCHARDS & VINEYARDS

Compact dimensions and a tight working footprint support movement between narrow crop rows.



LANDSCAPING & ESTATE CARE

Power steering and multiple tyre choices support mowing, grounds care and property maintenance.



LOADER & MATERIAL HANDLING

A heavy-duty front axle and responsive steering support loader and handling applications.



TILLAGE & IMPLEMENT WORK

Two PTO speeds, 4WD and Category I-N linkage support a broad range of compact implements.

S30 FEATURE PACKAGE

Useful equipment for efficient operation, easy control and everyday durability.

1.	Stage V three-cylinder engine	2.	9F+9R synchromesh shuttle
3.	Forward/reverse shuttle lever	4.	4WD heavy-duty front axle
5.	540 / 540E rear PTO	6.	Independent PTO
7.	1DA + 2DA optional remotes	8.	Power steering
9.	Wide, flat platform	10.	Metal bonnet and fenders
11.	Projector headlamps	12.	Foldable mid ROPS
13.	Telematics ready	14.	25 Km/h max speed

COMPACT SIZE.
SERIOUS CAPABILITY.



The S30 combines practical performance, operator comfort and implement flexibility in a compact package.

26 HP STAGE V ENGINE

The Mitsubishi three-cylinder engine delivers compact power with 1,319 cc displacement.

9F+9R SYNCHRO SHUTTLE

Eighteen speed combinations help match travel speed to the task and working conditions.

540 / 540E REAR PTO

Two PTO speeds provide flexibility for efficient operation with different implements.

S-COMFORT PLATFORM

Best in class, wide & open platform to comfortable driving experience

76.3 NM MAXIMUM TORQUE

Strong torque supports pulling performance and responsive implement work.

800 KG LIFTING CAPACITY

The rear hydraulic system handles a broad selection of compact mounted implements.

HEAVY-DUTY 4WD AXLE

A robust front axle supports traction articulation and demanding loader operations.

MULTIPLE TYRE OPTIONS

Agricultural, turf, industrial and Galaxy Pro options adapt the tractor to the job.

SPECIFICATIONS

FEATURES	S30 SHUTTLE XL
ENGINE	
Engine type	Mitsubishi, 3 cylinder
Power Category	26 HP
Displacement	1,319 cc
Rated speed	2,500 rpm
Maximum torque	76.3 Nm
Air cleaner / cold start	Dry type / Yes
Aspiration	Natural
HYDRAULICS	
Three-point linkage	CAT I-N
Rear lift capacity	775 Kg
Auxiliary circuit	1DA | 2DA (Opt.)
Hydraulic flow	18 L/min
TRANSMISSION	
Drive / Gear Box	4WD / 9F+9R Shuttle
Maximum speed	25 km/h
Front axle	Heavy-duty 4WD
DIMENSIONS	
Weight (W/o Driver)	1,340 kg
Wheelbase	1,570 mm
Total Length	2,461 mm
Total width / ROPS height	1,222 mm / 2,055 mm
Minimum ground clearance	234 mm
Front / rear track	855 mm / 930 mm

FEATURES	S30 SHUTTLE XL
BRAKES & STEERING	
Service brakes	Oil immersed
Differential lock	Foot Operated
Brake actuation	Mechanical
PTO	
Rear PTO	540 / 540E
PTO actuation	Mechanical
CAPACITIES	
Fuel Tank	20 L
ELECTRICAL	
Battery / alternator	12V 65Ah / 12V 42A

TYRE COMBINATIONS

AGRI (Std.)
6×12 | 8.30×20
WIDE RADIAL (Opt.)
7-12 | 300 / 70 R20
GALAXY PRO (Opt.)
220/55 R12 | 280/70 R16 240/60 R12 | 320/65 R18
TURF (Opt.)
25×8.50-14 | 13.60-16
INDUSTRIAL (Opt.)
23×8.50-12 | 33×15.50-16.5

INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No. 10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)
Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/522221
Fax:+91-01882-522222 | Email: info@solisworld.com | URL: www.solistractors.com