Solis

THE COMPACT HERO OF HIGH TORQUE

1568 cc
EFFICIENT
YANMAR ENGINE

132.2 Nm
MAXIMUM TORQUE

1,200 kg
HYDRAULIC LIFT

3 RANGE
HST TRANSMISSION

H40



More torque. More lift. Easier control for demanding compact work. Built for loader work, estate care, livestock operations and versatile implement applications.

Yanmar turbo power, effortless hydrostatic control and 1,200 kg lift capacity in one compact 4WD platform.

CAPABILITY ACROSS EVERY WORKING DAY

Strong torque, hydraulic flow and precise HST control support demanding jobs across farms, estates and properties.



LOADER & MATERIAL HANDLING

Optional 700 kg loader capacity and an integrated joystick support efficient loading and handling.



LIVESTOCK & FARMYARD WORK

Smooth forward/reverse pedals simplify repetitive movement around barns, yards and feed areas.



LANDSCAPING & ESTATE CARE

Compact dimensions, turf tyre options and precise speed control support grounds maintenance.



MOWING & IMPLEMENT WORK

Independent PTO, rear remotes and 1,200 kg lift capacity support a wide range of implements.

STANDARD H40 FEATURES

A complete compact tractor package for productive operation and everyday comfort.

1.	Yanmar turbo engine	2.	3-range HST
3.	Twin forward/reverse pedals	4.	Cruise control
5.	AutoThrottle	6.	Wet disc brakes
7.	Mechanical 4WD engagement	8.	Independent wet PTO clutch
9.	1DA + 2DA rear remotes	10.	Flat operator floor
11.	Bellows seat with armrests	12.	USB-C + wireless charging

HIGH TORQUE MEETS EFFORTLESS CONTROL



The H40 brings together Yanmar turbo performance, strong hydraulics and operator-focused technology.

YANMAR HIGH EFFICIENT & RELIABLE ENGINE

The 1,568 cc three-cylinder engine delivers 38 HP-class performance at 2,600 rpm.

OPERATOR COMFORT

Flat floor, bellows seat, armrests and well-positioned controls support longer working days.

CONNECTED CONVENIENCE

USB-C, wireless charging, 12 V socket and a 7-pin trailer socket support daily work.

AUTO THROTTLE

Maintains Engine RPM with ease, ensuring smoother and more convenient implement operations.

3-RANGE HST

Infinite speed control and separate forward/reverse pedals simplify precision manoeuvring.

1,200 KG HYDRAULIC LIFT

Position and draft control support a broad range of Cat-I mounted implements.

INDEPENDENT PTO

A switch-operated wet PTO clutch allows convenient PTO engagement and control.

UP TO 132.2 NM TORQUE

Peak torque at working engine speed supports stronger response under load.

SPECIFICATIONS

H40

FEATURES	H40
ENGINE	
Engine type	Yanmar, 3 cylinder
Power Category	38 HP class
Displacement	1.568 L
Rated speed	2,600 rpm
Maximum torque	121.6–132.2 Nm @ 1,690 rpm
Emissions	Stage V, DOC + DPF
Aspiration	Turbocharged
HYDRAULICS	
Hydraulic control	Position / Draft control
Rear linkage / lift	Cat-I / 1,200 kg
Remote valves	1DA + 2DA (Std.)
Implement flow	25.82 L/min
Steering flow	15.7 L/min
TRANSMISSION	
Drive / gearbox	4WD / 3-range HST
Differential lock	Mechanical pedal
Driving features	Cruise control / AutoThrottle
PTO	
Rear PTO	540 rpm
PTO clutch	Independent wet clutch
BRAKES & STEERING	
Service brakes	Wet disc
Brake actuation	Mechanical
Parking brake	Independent

FEATURES	H40
DIMENSIONS	
Weight	1,790 kg
Wheelbase	1,650 mm
Length / Width	3,325 / 1,460mm
Platform	Open deck with ROPS
Canopy	Optional
CAPACITIES	
Fuel Tank	38 L
ELECTRICAL	
Electrical conveniences	USB-C / wireless / 12 V socket



AGRI (Std.)
7-16 | 11.2-24 8-16 | 12.4-24
AGRI (Opt.)
7-16 | 9.5-24 7-16 | 11.2-24
AGRI (Opt.)
8-16 | 12.4-24
INDUSTRIAL / TURF (Opt.)
7×8.5-15 | 15-19.5 25-8.5-14 | 13.6-16

INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No. 10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)
Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/522221
Fax:+91-01882-522222 | Email: info@solisworld.com | URL: www.solistractors.com