Solis

FRONT PTO POWER. ALL-SEASON VERSATILITY.

26 HP
STAGE V POWER

600 kg
FRONT TPL LIFT

540 / 540E
REAR PTO

3 RANGE
HST TRANSMISSION

H26 HST



Front PTO and front linkage expand productivity for municipal, estate and specialist farm applications.

A compact Stage V tractor designed to operate front-mounted implements with smooth hydrostatic control.

FRONT PTO PRODUCTIVITY FOR EVERY SEASON

Front-mounted implements stay visible from the operator's seat and turn the 26 HST into a versatile year-round work partner.



FRONT MOWER

Maintain parks, estates, orchards and large lawns with a clear view of the cutting path.



SNOW BLOWER

Clear roads, yards and access routes efficiently with a front-mounted snow blower.



ROTARY BRUSH & SWEEPER

Remove leaves, debris and light snow from pathways, yards and municipal spaces.



FRONT + REAR COMBINATION

Operate compatible front and rear implements in one pass to increase daily productivity.

FRONT IMPLEMENT ADVANTAGE

Hydrostatic drive and front implement control make repeated manoeuvres easier and more precise.

1.	Front PTO application capability	2.	600 kg front TPL lift
3.	3-range HST transmission	4.	Clutch-free operation
5.	Cruise control	6.	AutoThrottle
7.	4WD heavy-duty front axle	8.	Power steering
9.	Maximum speed 25 km/h	10.	540 / 540E rear PTO
11.	775 kg rear lift	12.	1DA + 2DA hydraulic remotes

EFFORTLESS CONTROL. PRODUCTIVE PERFORMANCE.



The 26 HST combines smooth speed control, strong hydraulics and an operator-focused platform.

26 HP STAGE V ENGINE

A Mitsubishi three-cylinder engine delivers compact power at 2,500 rpm.

HEAVY-DUTY 4WD AXLE

Balanced steering and a robust front axle support traction and loader applications.

S-COMFORT PLATFORM

A wide, open platform and ergonomic controls provide easy entry and operating comfort.

AUTO THROTTLE

Engine RPM responds with pedal input to simplify operation and improve driving convenience.

3-RANGE HST

Clutch-free hydrostatic drive provides smooth speed control for precision and repetitive work.

775 KG REAR LIFT

Category I-N linkage handles a broad selection of compact mounted implements.

PROJECTOR HEADLAMPS

Quad projector lamps and rear work lights improve visibility for extended working hours.

76.3 NM MAXIMUM TORQUE

Strong torque supports responsive work with implements and changing terrain.

SPECIFICATIONS

FEATURES	H26 HST
ENGINE	
Engine type	Mitsubishi, 3 cylinder
Power Category	26 HP
Displacement	1,319 cc
Rated speed	2,500 rpm
Maximum torque	76.3 Nm
Air cleaner / cold start	Dry type / Yes
Aspiration	Natural
HYDRAULICS	
Three-point linkage	CAT I-N / 775 kg
Front TPL lift capacity	600 Kg
Auxiliary circuit	1DA (Std.) | 2DA (Opt.)
Hydraulic top link	Available
Hydraulic flow	18 L/min
TRANSMISSION	
Drive / Gear Box	4WD / 3-range HST
Maximum speed	25 km/h
Driving features	Cruise control / AutoThrottle
DIMENSIONS	
Weight (W/o Driver)	1,250 kg
Wheelbase	1,570 mm
Total Length	2,461 mm
Total width / ROPS height	1,215 mm / 2,325 mm
Minimum ground clearance	240 mm
Front / rear track	855 mm / 930 mm

FEATURES	H26 HST
BRAKES & STEERING	
Service brakes	Oil immersed
Differential lock	Foot Operated
Brake actuation	Mechanical
PTO	
Rear PTO	540 / 540E rpm
PTO actuation	Mechanical
CAPACITIES	
Fuel Tank	22 L
ELECTRICAL	
Battery / alternator	12V 65Ah / 12V 42A



AGRI (Std.)
6×12 | 8.3-20
AGRI (Opt.)
7-14 + 8.3×24
GALAXY PRO (Opt.)
220/55 R12 | 280/70 R16
WIDER TURF / INDUSTRIAL (Opt.)
25×8.5-14 | 13.6-16
TURF / INDUSTRIAL (Opt.)
23×8.5-12 | 33×15.5-16.5

INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No. 10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)
Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/522221
Fax:+91-01882-522222 | Email: info@solisworld.com | URL: www.solistractors.com