














SPECIFICATION

FEATURES	26 SHUTTLE XL
ENGINE	
Engine Type	3-Cylinder Diesel Engine
HP Category	26
No. of Cylinders	3
Aspiration	Naturally
Cubic Capacity (cc)	1319
Rated RPM (+/-25mm)	2500
Air Cleaner	Dry
Cold Start	Standard
Max Torque (Nm)	76.3
Exhaust	Silencer in the engine compartment, downward discharge
TRANSMISSION	
Drive	4 WD
Clutch	Single Clutch
Gearbox	9 Forward + 9 Reverse
Front Axle	Heavy Duty
Transmission	Constant Mesh with Synchromesh Shuttle Lever
SPEED (FORWARD)	
Maximum Speed (Km/Hr)	21.46 @2760 fly up
Minimum Speed (Km/Hr)	1.14@rated
BRAKES	
Brakes	Oil Immersed
Type of Actuation	Mechanical
Parking Brake	Independent
DIFFERENTIAL LOCK	
Differential Lock	Yes, Foot Operated
PTO	
PTO (rpm)	540/540E
PTO (actuation)	Mechanical
STEERING	
Steering	Power steering
ELECTRICAL	
Battery	12V, 65 Ah
Alternator	12V, 42 A
Seven Pin Trailer Socket	Standard
HYDRAULICS	
3 Point Linkage	Cat 1-N
Stay Bars	Anchor Chain

FEATURES	26 SHUTTLEXL		
Additional hydraulic circuit	1DA (ROPS)/ 2DA (CABIN)		
Hydraulic Lifting Capacity (Kg)	775		
Lift Rods	Standard		
Litre Per Minute (LPM)	17.8		
SAFETY SWITCH 			
PTO Safety	Standard		
Neutral Safety Switch	Standard		
Clutch Safety Switch	Standard		
CAPACITY (LTRS)(+/-5%) 			
Fuel Tank (Lit)	22(ROPS), 26(CABIN)		
TURNING RADIUS 			
Without brakes (m) as per standard tyres	3.02 (RHS), 3.15 (LHS)		
TYRE 			
Front	6.00-12		
Rear	8.30-20		
DIMENSION & WEIGHT(+/-5%) 			
Weight (Kg)	1250		
Wheel Base (mm)	1570		
Total Length (mm)	2895		
Total Width (mm)	1215 (max)-1050 (min)		
Height (mm) Up to ROPS	2325		
Min Ground Clearance (mm)	240		
Front Track (mm)	885		
Rear Track (mm)	960		
OTHERS 			
Fuel Indicator Gauge	Standard		
Front Tow Hook	Standard		
Front & Rear Weights with std. Ballast	Front weights-2 x 15		
Trailer Hitch	1. E-marked swinging drawbar 2. Clevis Hitch 3. Semi-Automatic hitch		
ROPS	Yes		
OPTIONAL FEATURES 			
Cabin Option	Optional only heater		
TYRES			
 Radial Agri: Front Rear 6.5/80-12 280/70 R18	 Turf: Front Rear 25x8,50-14 13.60-16	 Ind: Front Rear 23x8,50-12 33x15,50-16,5	 Galaxy Pro: Front Rear FT - 220/55R12 RT - 280/70R16
Additional Bias Tyre		Front Tyre: 7*14 Rear Tyre: 8.3-24	
Front Loader		YES optional	

**Data and specifications are subject to change without any advance notice due to continuous product improvement and development.