BIG CAPABILITY LOW PROFILE

60 HP
STAGE V POWER

242 Nm
TORQUE AT 1,400 RPM

2,500 kg
REAR LIFT

45 L/min
HYDRAULIC FLOW

LP60



Built to move confidently through orchards, covered cultivation, livestock yards and mixed-farm duties.

60 HP Stage V power with strong low-speed torque and serious implement capacity for specialised farms

CAPABILITY THAT FITS THE FARM

LP60 combines a low working profile with the traction, PTO and hydraulic capacity needed across specialist and utility work.



ORCHARDS & WIDER VINEYARD ROWS

Low bonnet height, 4WD and power steering support inter-row mowing, spraying and cultivation.



POLYTUNNELS & COVERED CROPS

A low operator and fender profile helps access protected cultivation. Confirm structure clearance before entry.



LIVESTOCK FARMS & YARDS

Synchro shuttle, compact dimensions and strong lift capacity suit frequent manoeuvring and daily implement work.



ESTATES & GROUND CARE

Dual-speed PTO and 45 L/min hydraulics support mowing, maintenance and seasonal utility tasks.

L60 FEATURE PACKAGE

- Inhouse S-Tech Engine- 3 Cy. Stage V 60 HP Engine
- Efficient cooling package with better serviceability
- 65 Liters fuel tank-under floor
- Sealed Firewall for heat protection
- Tilt and telescopic steering wheel
- Spacious platform for operator comfort
- Hand Throttle Electronic
- Mid ROPS
- Heavy Duty Three Point Linkage
- Mita Hydraulic with PC/DC
- 2DA/3DA (opt.)
- Hydraulic Flow 45 LPM
- Rear View window for implements
- Carraro Front axle- 4WD
- Telematics
- Aerodynamic Front Hood
- Button operated liftomatic

POWER WHERE THE WORK HAPPENS



The LP60 pairs usable torque with a straightforward drivetrain and implement-ready hydraulics.

STRONG LOW-SPEED TORQUE

242 Nm at 1,400 rpm from the 3 L Stage V engine.

2,500 KG REAR LIFT

CAT II linkage, 45 L/min flow and two DA remotes standard.

OPERATOR-FOCUSED CONTROL

Wide workspace, power steering and adjustable steering column.

HIGH-OUTPUT LIGHTING

Quad projector lamps support clear visibility during longer days.

12+12 SYNCHRO SHUTTLE

Creeper configuration and multiple speeds for precise work.

DUAL-SPEED PTO

540 and 540E/1000 speeds help match power to the implement.

HEAVY-DUTY FRONT AXLE

Sealed 4WD axle with strong casing and improved articulation.

MUTIPLE HITCH OPTIONS

E-Market Swinging Drawbar, Semi- Automatic Clevis Hitch, Cuna Hitch, Automatic clevis Hitch

SPECIFICATIONS — LP60

FEATURES	LP60
ENGINE	
Cylinders / capacity	3 / 3,065 cc
Power Category	60 HP
Rated speed	2,000 rpm
Maximum torque	242 Nm
Aspiration / air cleaner	Natural Aspired/ Stage V
HYDRAULICS	
Three-point linkage	CAT II N
Rear lift capacity	2,500 kg
Hydraulic flow	45 L/min
Auxiliary circuit	2 DA (Std.) / 3 DA (Opt.)
TRANSMISSION	
Drive / Gear Box	4WD / 12F + 12R
Maximum speed	30 km/h
Minimum speed	0.5 km/h
Type	Synchro shuttle, creeper
PTO	
Rear / mid PTO	540 / 540E, 6 Spline
BRAKES & STEERING	
Service brakes	Oil immersed, mechanical
Differential lock	Foot operated
Steering	Power steering
CAPACITIES	
Fuel Tank	65 L
STANDARD TYRES	
Front / rear	280/70 R18 | 340/85 R28

FEATURES	LP60
DIMENSIONS	
Wheelbase	2160 (mm)
Length / width	4075 (mm) / 1715 (mm)
Height upto ROPS	2300 (mm)
Ground Clearance	275 (mm)
Weight	1,830 (kg)
Turning radius	4.2 m (w/o breaks)
OTHERS	
Trailer Hitch	E market Swinging Drawbar Semi- Automatic Clevis Hitch Cuna Hitch Automatic Clevis Hitch
Front tow hook	Yes
Additional Weights	F: 50 + 25×4 R: 34×1 each



TYRE COMBINATIONS
260/70 R16 | 360/70 R24 (Opt.)
280/70 R18 | 420/70 R24 (Opt.)
280/70 R18 | 360/70 R28 (Std.)
280/70 R18 | 380/85 R28 (Opt.)

INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No. 10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)
Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/522221
Fax:+91-01882-522222 | Email: info@solisworld.com | URL: www.solistractors.com