

Technical specifications

Engine		F50Cn / F50Chn
Manufacturer, Model, Engine HP(kW)-Gross		TYM, T2300N2, 48(36)
Rated engine speed (RPM)		2,600
Number of cylinders		4
Displacement (cc)		2,287
Air cleaner, PTO HP(kW)		Single Dry, 40(29.8)
Alternator		12V, 50A
Fuel System Type		Indirect Fuel Injection
Drivetrain		
Transmission Type		Synchro-Shuttle HST
Number of speed		F12/R12 3 Range
Max traveling speed (km/h)		26.8 27.2
Brakes, Steering		Wet Disc,Hydrostatic
Clutch		Dry single plate N/A
Hydraulic system		
hitch lift capacity (kg)		1,500
at24 inches behind link ends (kg)		757
Lift control type		Position/Draft
No.of standard remote valves(Loader - Rear)		4-4
PTO		
Rear(RPM)		540/540E
Capacities		
Fuel tank (L)		30
Dimension(with standard tires)		
Overall length (mm) with 3P		3,429
Overall width (mm)		1,477
Wheelbase (mm)		1,670
Height (mm)		2,255
Min Ground Clearance (mm)		443.5
Min Turning Radius (mm) with brakes		2,550
Min Turning Radius (mm) w/o brakes		2,920
Total Weight (kg)		1,711 1,702
Standard Tires		
Agricultural Front		7.0-16
Agricultural Rear		11.2-24
Turf Front		27x8.5-15
Turf Rear		41x14-20
Industrial Front		215/70R16
Industrial Rear		11.2-24