

Technical specifications

Engine		6225R/6225H
Manufacturer, Model, Engine HP(kW)-Gross		TYM, T2300T3, 57.3(43)
Rated engine speed (RPM)		2,600
Number of cylinders		4
Displacement (cc)		2,287
Air cleaner, PTO HP(kW)		Single Dry, 52.9(39.7) 50.4(37.8)
Alternator		12V, 50A
Fuel System Type		Indirect Fuel Injection
Drivetrain		
Transmission Type		Synchrom-Shuttle HST
Number of speed		F12/R12 3 Range
Max traveling speed (km/h)		28.8 28.7
Brakes, Steering		Wet Disc,Hydrostatic
Clutch		Dry single plate N/A
Hydraulic system		
hitch lift capacity (kg)		1,456
at24 inches behind link ends (kg)		937
Lift control type		Position/Draft
No.of standard remote valves(Loader - Rear)		4-4
PTO		
Rear(RPM)		540/540E
Capacities		
Fuel tank (L)		45
Dimension(with standard tires)		
Overall length (mm) with 3P		3,421
Overall width (mm)		1,814
Wheelbase (mm)		1,806
Height (mm)		2,500
Min Ground Clearance (mm)		391
Min Turning Radius (mm) with brakes		2,390
Min Turning Radius (mm) w/o brakes		2,850
Total Weight (kg)		1,795 1,802
Standard Tires		
Agricultural Front		9.5-16
Agricultural Rear		13.6-26
Turf Front		29x12.5-15
Turf Rear		44x18-20
Industrial Front		305/70-16
Industrial Rear		17.5Lx24