

Technical specifications

Engine		T78SM/T78SC
Manufacturer, Model, Engine HP(kW)-Gross		DEUTZ, TCD2.9L4, 74 (55.4)
Rated engine speed (RPM)		2,200
Number of cylinders		4
Displacement (cc)		2,925
Air cleaner, PTO HP(kW)		Dual Dry, 64.8(48.6)
Alternator		12V, 95A
Fuel System Type		CRDI
Drivetrain		
Transmission Type		Synchro-Shuttle Power Shuttle
Number of speed		F16/R16(creep interlock)
Max traveling speed (km/h)		36.6
Brakes, Steering		Wet Disc, Hydrostatic
Clutch		Dry single plate Wet multi plate
Hydraulic system		
hitch lift capacity (kg)		2,338
at 24 inches behind link ends (kg)		1,579
Lift control type		Position/Draft
No. of standard remote valves (Loader - Rear)		4-4
PTO		
Rear (RPM)		540/540E
Capacities		
Towing Capacity (kg)		904 - 1,853
Fuel tank (L)		90
Dimension (with standard tires)		
Overall length (mm) with 3P		4,269
Overall width (mm)		2,345
Wheelbase (mm)		2,188
Height (mm)		2,664
Min Ground Clearance (mm)		467
Min Turning Radius (mm) with brakes		3,700
Min Turning Radius (mm) w/o brakes		4,135
Total Weight (kg)		3,091
Standard Tires		
Agricultural Front		11.2-24
Agricultural Rear		16.9-30
Turf Front		-
Turf Rear		-
Industrial Front		-
Industrial Rear		-