

Technical specifications

| Engine | | T68SM/T68SC |
|---|--|------------------------------------|
| Manufacturer, Model, Engine HP(kW)-Gross | | DEUTZ, TCD2.9L4, 67(50) |
| Rated engine speed (RPM) | | 2,200 |
| Number of cylinders | | 4 |
| Displacement (cc) | | 2,925 |
| Air cleaner, PTO HP(kW) | | Dual Dry, 61.3(46) |
| Alternator | | 12V, 95A |
| Fuel System Type | | CRDI |
| Drivetrain | | |
| Transmission Type | | Synchro-Shuttle Power Shuttle |
| Number of speed | | F24/R24 |
| Max traveling speed (km/h) | | 36.9 |
| Brakes, Steering | | Wet Disc, Hydrostatic |
| Clutch | | Dry single plate Wet multi plate |
| Hydraulic system | | |
| hitch lift capacity (kg) | | 1,964 |
| at 24 inches behind link ends (kg) | | 1,433 |
| Lift control type | | Position/Draft |
| No. of standard remote valves (Loader - Rear) | | 4-4 |
| PTO | | |
| Rear (RPM) | | 540/540E/1,000 |
| Capacities | | |
| Towing Capacity (kg) | | 1,145 - 1,790 |
| Fuel tank (L) | | 70 |
| Dimension (with standard tires) | | |
| Overall length (mm) with 3P | | 3,982 |
| Overall width (mm) | | 1,952 |
| Wheelbase (mm) | | 2,155 |
| Height (mm) | | 2,615 |
| Min Ground Clearance (mm) | | 440 |
| Min Turning Radius (mm) with brakes | | 3,590 |
| Min Turning Radius (mm) w/o brakes | | 4,120 |
| Total Weight (kg) | | 2,851 |
| Standard Tires | | |
| Agricultural Front | | 11.2-20 |
| Agricultural Rear | | 14.9-30 |
| Turf Front | | - |
| Turf Rear | | - |
| Industrial Front | | - |
| Industrial Rear | | - |