

Technical specifications

Engine	2500/2500H	2500L / 2500HL
Manufacturer, Model, Engine HP(kW)-Gross	TYM, T1100N2,24(18)	TYM, T1100N2,24(18)
Rated engine speed (RPM)	2,800	2,800
Number of cylinders	3	3
Displacement (cc)	1,175	1,175
Air cleaner, PTO HP(kW)	Single Dry, 20.7(15.5)	Single Dry, 20.7(15.5) 18(13.5)
Alternator	12V,60A	12V, 60A
Fuel System Type	Indirect Fuel Injection	Indirect Fuel Injection
Drivetrain		
Transmission Type	Synchro-Shuttle HST	Synchro-Shuttle HST
Number of speed	F6/R2 2 Range	F6/R2 2 Range
Max traveling speed (km/h)	19.2 21.5	21.9 24.6
Brakes, Steering	Wet Disc, Hydrostatic	Wet Disc, Hydrostatic
Clutch	Dry Single Plate	Dry Single Plate
Hydraulic system		
hitch lift capacity (kg)	512	512
at 24 inches behind link ends (kg)	328	328
Lift control type	Position	Position
No. of standard remote valves (Loader - Rear)	Optional(2)	Optional(2)
PTO		
Rear (RPM)	540 / 1,000	540 / 1,000
Capacities		
Fuel tank (L)	23	23
Dimension (with standard tires)		
Overall length (mm) with 3P	3,055	3,124
Overall width (mm)	1,321	1,419
Wheelbase (mm)	1,502	1,672
Height (mm)	2,253	2,330
Min Ground Clearance (mm)	375	417
Min Turning Radius (mm) with brakes	2,240	2,700
Min Turning Radius (mm) w/o brakes	2,700	2,240
Total Weight (kg)	888 905	988 1,031
Standard Tires		
Agricultural Front	6.0-12	6.0-12
Agricultural Rear	9.5-16	9.5-16
Turf Front	23x8.5-12	23x8.5-12
Turf Rear	33x12.5-16.5	33x12.5-16.5
Industrial Front	23x8.5-12	25x8.5-12
Industrial Rear	12-16.5	33x12.5-16.5