

Technical specifications

Engine		F50Rn/F50hn
Manufacturer, Model, Engine HP(kW)-Gross		TYM, T2300N2, 48(36)
Rated engine speed (RPM)		2,600
Number of cylinders		4
Displacement (cc)		2,287
Air cleaner, PTO HP(kW)		Single Dry, 40(29.8)
Alternator		12V, 50A
Fuel System Type		Indirect Fuel Injection
Drivetrain		
Transmission Type		Synchro-Shuttle HST
Number of speed		F12/R12 3 Range
Max traveling speed (km/h)		28.7 28.4
Brakes, Steering		Wet Disc,Hydrostatic
Clutch		Dry single plate N/A
Hydraulic system		
hitch lift capacity (kg)		1,500
at24 inches behind link ends (kg)		757
Lift control type		Position/Draft
No.of standard remote valves(Loader - Rear)		2-2
PTO		
Rear(RPM)		540/540E
Capacities		
Fuel tank (L)		30
Dimension(with standard tires)		
Overall length (mm) with 3P		3,429
Overall width (mm)		1,491
Wheelbase (mm)		1,670
Height (mm)		2,515
Min Ground Clearance (mm)		443.5
Min Turning Radius (mm) with brakes		2,550
Min Turning Radius (mm) w/o brakes		2,920
Total Weight (kg)		1,548 1,539
Standard Tires		
Agricultural Front		8.0-16
Agricultural Rear		12.4-24
Turf Front		27x8.5-15
Turf Rear		41x14-20
Industrial Front		10-16.5
Industrial Rear		420/70R24