## ARTICULATED MINI BACKHOE LOADER **BLD6** hydrostatic





#### **EN** USAGE AND CHARACTERISTICS

- The BLD6 is a mini articulated chassis wheel backhoe-loader known for its compact design and versatility and can be used for all kinds of unusual jobs.
- Ergonomic seat with 180° rotation for easy use of the excavator.
- Two safety legs, hydraulically independent for maximum stability during excavation.
- The wheelbase, the limited external width of 1.15m and the articulated frame, make it very flexible even on the narrowest paths.
- $\bullet \ \ Perkins\ 25hp/2600rpm\ three-cylinder\ water-cooled\ diesel\ engine,\ new\ generation\ STAGE\ V\ low\ fuel\ consumption.$
- A larger and stronger lifting cylinder guarantees that the load distribution is always optimally transferred to the loading arm offering maximum stability.
- The angle loading arm is designed to be particularly robust and torsionally resistant. The advantage of P-kinematics lies
  in the precise parallel movement throughout the lifting range.
- · New high standard canopy with increased visibility
- Euro-hitch Brackets makes implements connection simple.
- The steering column can be adjusted based on the operator and ensures ergonomic handling without fatigue.
- Ergonomic Joystick robust and sensitive at the same time. In this way, you are always in control of the machine and its basic functions.
- · Powerful hydraulic pump Hengli USA.
- Third Hydraulic supply line on the boom for future connection of other accessories (dual power line).
- Compact cast counterweight on the back successfully improves performance.
- Lifting force 600kg.
- · Includes a bucket 1150mm.
- Electric start with 12V starter.
- EC Conformity.

M	€	KG	hp	# mm		L/min	<b>a</b>	(Market)	
BLD6		2280	Diesel Perkins 25.4	1150	4900/1150/2350	56	250	12	

CROCO120 EHF700 EHB120 4in1 EHG1200 LD6SNOW LD6AUGER

# GRAECUS ARTICULATED SMALL LOADER LD07 HST & T-LD07 HST



#### **EN** USAGE AND CHARACTERISTICS

- Maximum load capacity 900kg, maximum lifting load capacity 600kg.
- Maximum lift (at pin): LD07 2550mm, T-LD07 3184mm.
- Perkins 25hp/2600rpm three-cylinder water-cooled diesel engine, new generation STAGE V low fuel consumption.
- Mini wheel loader known for its compact design and versatility and can be used for all kinds of unusual jobs. The T-LD07
  model has an additional robust telescopic boom with greater lift.
- The wheelbase, limited 1.15m external width and articulated frame make it very versatile even on the narrowest paths with an external turning radius of 1989mm.
- The angled loading arm is designed to be particularly robust and torsion resistant. The advantage of P-kinematics lies in
  the precise parallel movement over the entire lifting range.
- Ergonomic joystick robust and sensitive at the same time. All movements on the same joystick even on the telescopic, this way you have full control of the machine and its basic functions
- Top performance with the Italian PWG guarantee, hydrostatic gearbox, hydraulic pump, hydraulic steering and hydraulic traveling system.
- Third hydraulic supply line (dual energy line) for connecting additional accessories in the future.
- A larger and more powerful hydraulic lifting piston guarantees that the load distribution is always optimally transferred to the loading arm offering maximum stability.
- · High-spec, new style canopy that improves safety and visibility.
- Easy transport even with small vehicles thanks to the low weight of 1470kg.
- Cast counterweight at the rear, significantly improves the stability of the loader.
- · The steering column can be adjusted based on the operator and ensures ergonomic handling without fatigue.
- Using the Euro-hitch fast coupling, attachments can be mounted quickly.
- Includes a bucket 1200mm.
- EC Conformity.

M	€	<mark>€</mark>	hp	<b>₽₽₽</b> kg	# mm	<del>/</del>	L/min	<b>S</b>	(Market)
LD07 HST		1500	Diesel Perkins 25 / 2600rpm	600	1200	3325/1155/2360	39.2	160	18
T-LD07 HST		1700	Diesel Perkins 25 / 2600rpm	600	1200	3325/1155/2360	39.2	160	18

CROCO120 EHF700 EHB120 4in1 EHG1200 LD6SNOW LD6AUGER

### ARTICULATED SMALL LOADER LD10 HST





#### **EN** USAGE AND CHARACTERISTICS

- Maximum load capacity 1600kg, maximum lifting load capacity 900kg.
- Maximum lift (at pin): 2678mm.
- Perkins 25hp/2600rpm three-cylinder water-cooled diesel engine, new generation STAGE V low fuel consumption.
- · Mini wheel loader known for its compact design and versatility and can be used for all kinds of unusual jobs.
- The wheelbase, limited 1446mm external width and articulated frame make it very versatile even on the narrowest
  paths with an internal turning radius of 1869mm and an external turning radius of 3172mm..
- The angled loading arm is designed to be particularly robust and torsion resistant. The advantage of P-kinematics lies in the precise parallel movement over the entire lifting range.
- Ergonomic joystick robust and sensitive at the same time. All movements on the same joystick even on the telescopic, this way you have full control of the machine and its basic functions
- Top performance with the Italian PWG guarantee, hydrostatic gearbox, hydraulic pump, hydraulic steering and hydraulic traveling system.
- Third hydraulic supply line (dual energy line) for connecting additional accessories in the future.
- A larger and more powerful hydraulic lifting piston guarantees that the load distribution is always optimally transferred to the loading arm offering maximum stability.
- · High-spec, new style canopy that improves safety and visibility.
- Cast counterweight at the rear, significantly improves the stability of the loader.
- · The steering column can be adjusted based on the operator and ensures ergonomic handling without fatigue.
- Using the Euro-hitch fast coupling, attachments can be mounted quickly.
- Includes a bucket 1600mm.
- EC Conformity.



CROCO160 EHF1200 EHB160 4in1 EHG1200 LD10SNOW LD10AUGER



# ARTICULATED SMALL LOADER **T-LD10 HST** telescopic



#### **EN** USAGE AND CHARACTERISTICS

- Maximum load capacity 1500kg, maximum lifting load capacity 900kg.
- Maximum lift (at pin): 3446mm.
- Perkins 25hp/2600rpm three-cylinder water-cooled diesel engine, new generation STAGE V low fuel consumption.
- 2-speed selectable slow-fast with Hi-Lo switch.
- Mini wheel loader known for its compact design and versatility and can be used for all kinds of unusual jobs. The T-LD10 model has an extra robust telescopic arm with a higher lift.
- The wheelbase, limited 1349mm external width and articulated frame make it very versatile even on the narrowest
  paths with an internal turning radius of 1360mm and an external turning radius of 2795mm..
- The angled loading arm is designed to be particularly robust and torsion resistant. The advantage of P-kinematics lies in the precise parallel movement over the entire lifting range.
- Ergonomic joystick robust and sensitive at the same time. All movements on the same joystick even on the telescopic, this way you have full control of the machine and its basic functions
- Top performance with the Italian PWG guarantee, hydrostatic gearbox, hydraulic pump, hydraulic steering and hydraulic traveling system.
- Third hydraulic supply line (dual energy line) for connecting additional accessories in the future.
- A larger and more powerful hydraulic lifting piston guarantees that the load distribution is always optimally transferred to the loading arm offering maximum stability.
- · High-spec, new style canopy that improves safety and visibility.
- Cast counterweight at the rear, significantly improves the stability of the loader.
- The steering column can be adjusted based on the operator and ensures ergonomic handling without fatigue.
- Using the Euro-hitch fast coupling, attachments can be mounted quickly.
- Includes a bucket 1600mm.
- EC Conformity.



CROCO160 EHF1200 EHB160 4in1 EHG1200 LD10SNOW LD10AUGER

### ARTICULATED SMALL LOADER LD11





#### **EN** USAGE AND CHARACTERISTICS

- Maximum load capacity 1700kg, maximum lifting load capacity 1000kg.
- Maximum lift (at pin): 2604mm.
- · Changchai 51hp/2650rpm three-cylinder water-cooled diesel engine, new generation STAGE V with low consumption.
- · 2-speed selectable slow-fast with Hi-Lo switch.
- · Mini wheel loader known for its compact design and versatility and can be used for all kinds of unusual jobs.
- The wheelbase, limited 1520mm external width and articulated frame make it very versatile even on the narrowest
  paths with an internal turning radius of 2200mm and an external turning radius of 3950mm.
- The angled loading arm is designed to be particularly robust and torsion resistant. The advantage of P-kinematics lies in the precise parallel movement over the entire lifting range.
- Ergonomic joystick robust and sensitive at the same time. All movements on the same joystick even on the telescopic, this way you have full control of the machine and its basic functions
- Top performance with the Italian PWG guarantee, hydrostatic gearbox, hydraulic pump, hydraulic steering and hydraulic traveling system.
- Third hydraulic supply line (dual energy line) for connecting additional accessories in the future.
- A larger and more powerful hydraulic lifting piston guarantees that the load distribution is always optimally transferred to the loading arm offering maximum stability.
- · High-spec, new style canopy that improves safety and visibility.
- Cast counterweight at the rear, significantly improves the stability of the loader.
- The steering column can be adjusted based on the operator and ensures ergonomic handling without fatigue.
- Using the Euro-hitch fast coupling, attachments can be mounted quickly.
- · Includes a bucket 1600mm.
- EC Conformity.



CROCO160 EHF1200 EHB160 4in1 EHG1200 LD10SNOW LD10AUGER



# ARTICULATED SMALL LOADER **T-LD11** telescopic



#### **EN** USAGE AND CHARACTERISTICS

- Maximum load capacity 1700kg, maximum lifting load capacity 1000kg.
- Maximum lift (at pin): 3442mm.
- Changchai 25hp/2600rpm three-cylinder water-cooled diesel engine, new generation STAGE V with low consumption.
- 2-speed selectable slow-fast with Hi-Lo switch.
- Mini wheel loader known for its compact design and versatility and can be used for all kinds of unusual jobs. The T-LD11
  model has an extra robust telescopic arm with a higher lift.
- The wheelbase, limited 1520mm external width and articulated frame make it very versatile even on the narrowest paths
  with an internal turning radius of 2200mm and an external turning radius of 3950mm.
- The angled loading arm is designed to be particularly robust and torsion resistant. The advantage of P-kinematics lies in
  the precise parallel movement over the entire lifting range.
- Ergonomic joystick robust and sensitive at the same time. All movements on the same joystick even on the telescopic, this
  way you have full control of the machine and its basic functions
- Top performance with the Italian PWG guarantee, hydrostatic gearbox, hydraulic pump, hydraulic steering and hydraulic traveling system.
- Third hydraulic supply line (dual energy line) for connecting additional accessories in the future.
- A larger and more powerful hydraulic lifting piston guarantees that the load distribution is always optimally transferred to the loading arm offering maximum stability.
- · High-spec, new style canopy that improves safety and visibility.
- Cast counterweight at the rear, significantly improves the stability of the loader.
- · The steering column can be adjusted based on the operator and ensures ergonomic handling without fatigue.
- · Using the Euro-hitch fast coupling, attachments can be mounted quickly.
- Includes a bucket 1600mm.
- EC Conformity.



CROCO160 EHF1200 EHB160 4in1 EHG1200 LD10SNOW LD10AUGER

# ARTICULATED SMALL LOADER **T-LD13** telescopic





#### **EN** USAGE AND CHARACTERISTICS

- Maximum load capacity 2200kg, maximum lifting load capacity 1300kg.
- Maximum lift (at pin): 4129mm.
- $\bullet \ \ Yunnei\ 51hp/2650rpm\ three-cylinder\ water-cooled\ diesel\ engine,\ new\ generation\ STAGE\ V\ with\ low\ consumption.$
- 2-speed selectable slow-fast with Hi-Lo switch.
- Mini wheel loader known for its compact design and versatility and can be used for all kinds of unusual jobs. The T-LD13
  model has an extra robust telescopic arm with a higher lift.
- The wheelbase, limited 1760mm external width and articulated frame make it very versatile even on the narrowest paths
  with an internal turning radius of 2920mm and an external turning radius of 4680mm.
- The angled loading arm is designed to be particularly robust and torsion resistant. The advantage of P-kinematics lies in
  the precise parallel movement over the entire lifting range.
- Ergonomic joystick robust and sensitive at the same time. All movements on the same joystick even on the telescopic, this way you have full control of the machine and its basic functions
- Top performance with the Italian PWG guarantee, hydrostatic gearbox, hydraulic pump, hydraulic steering and hydraulic traveling system.
- Third hydraulic supply line (dual energy line) for connecting additional accessories in the future.
- A larger and more powerful hydraulic lifting piston guarantees that the load distribution is always optimally transferred to the loading arm offering maximum stability.
- · High-spec, new style canopy that improves safety and visibility.
- Cast counterweight at the rear, significantly improves the stability of the loader.
- The steering column can be adjusted based on the operator and ensures ergonomic handling without fatigue.
- · Using the Euro-hitch fast coupling, attachments can be mounted quickly.
- Includes a bucket 1600mm.
- EC Conformity.



CROCO180
EHF1200
EHB180 4in1
EHG1200
LD10SNOW
LD10AUGER

Κλαδοσυλλέκτης Forks Bucket 4 in 1 Bale grapper Snowplow Post hole digger