



EN USAGE AND CHARACTERISTICS

- 4-stroke gasoline engines, electric starter for the shredder and manual starter for the damper.
- Semi-automatic feed with slope.
- The anti-vibration clutch minimizes direct movement between the engine and the drum, facilitating cold start and protecting the crank in the event of a cutting system jam.
- Folding hopper to protect and reduce the space required during storage / transport.
- Anti-fouling spray duct design. Easy rotation of the launch line 360°.
- Drum cutting system with 2 double profile knives plus 1 fixed, high hardening to adjust the cutting thickness.
- Long life bearing.
- Transmission with Kevlar belts.
- The ejection distance is adjusted by the door at the top of the duct.
- The package includes a 300kg transport box transforming the into a dumper and now into the ultimate shredder.
- Durable and reliable gearbox 3 front + 1 rear.
- The tracks allow its use in up to 30% inclination and loading and transport capacity up to 300kg.
- Low center of gravity and proper load distribution ensure maximum stability in any terrain.
- Independent clutch and disengagement levers on each wheel that contribute to easy change of course and on-site rotation.
- Automatic parking brake offers maximum safety.
- Fully ergonomic controls, easy to use, guarantee exceptional flexibility and precise control.
- 5 mm metal guard at the bottom to protect the engine and transmission.
- Fully made of high-strength metals. Reinforcement hollow section at the bottom, make it suitable for any load or pressure.
- Operation with safety system and emergency button for immediate shutdown.
- EC Conformity.

M	€							
			θρυμματιστής	ντάμπερ		mm	mm	L/h
KBD12	325		Loncin 420cc 15 hp	Lifan 196cc 6.5 hp	180/60/34	1900/640/1600	910/600/204	1,0
KBD12-BS	325		Briggs & Stratton 420cc 15 hp	Briggs & Stratton 208cc 6.5 hp	180/60/34	1900/640/1600	910/600/204	1,0

ACCESSORIES













Gift : transport platform 1040/860/204 mm



GRAECUS



- 4-stroke gasoline engine, start with electric starter.
- Semi-automatic feed with slope.
- The anti-vibration clutch minimizes direct movement between the engine and the drum, facilitating cold start and protecting the crank in the event of a cutting system jam.
- Drum cutting system with 2 double profile knives plus 1 fixed, high hardening to adjust the cutting thickness.
- Anti-fouling spray duct design.
- The ejection distance is adjusted by the door at the top of the duct.
- Long life bearing.
- Adjust the cutting thickness from the knife at the bottom.
- Double-edged knives can be reversed if needed.
- Large wheels and towbar for four-wheel ATV, UTV and car.
- Transmission with Kevlar belts.
- Operation with safety system and emergency button for immediate shutdown.
- Height-adjustable support bracket with wheel for easy disconnection and storage.
- EC Conformity.

											
M	€	kg	hp	mm	m ³ /h	no.	mm	mm	no.	L/h	
KBT10		116	Loncin 196cc 6.5 hp	1750/550/1050	3	2+1	5-15	60-100	2	0.8 L/h	Recoil starter

ACCESSORIES








M	€										
KBT12		260	hp Loncin 420cc 15 hp	mm 1000/2270/1655	m ³ /h 6-7	no. 2+1	mm 5-15	mm 80-120	no. 2	L/h 1 L/h	Electrical starter















EN USAGE AND CHARACTERISTICS

- 4-stroke gasoline engine, start with electric starter.
- Semi-automatic feed with slope.
- Easily accessible impeller without the use of tools.
- Easy rotation of the ejection duct 360°.
- The anti-vibration clutch minimizes direct movement between the engine and the drum, facilitating cold start and protecting the crank in the event of a cutting system jam.
- Anti-fouling spray duct design.
- The ejection distance is adjusted by the door at the top of the duct.
- Long life bearing.
- Adjust the cutting thickness from the knife at the bottom.
- Double-edged knives can be reversed if needed.
- Large wheels and towbar for four-wheel ATV, UTV and car.
- Transmission with Kevlar belts.
- Operation with safety system and emergency button for immediate shutdown.
- Height-adjustable support bracket with wheel for easy disconnection and storage.
- EC Conformity.

M	€										
		kg	hp	mm	m ³ /h	no.	mm	mm	no.	L/h	
KBT15H		700	Loncin 764cc 25 hp	1390/3470/2280	23	2+1	5-15	150	2	1.4 L/h	Electrical starter



- 4-stroke gasoline engine, with recoil starter.
- Semi-automatic feed with slope.
- Drum cutting system with 2 double profile knives plus 1 fixed, high hardening to adjust the cutting thickness.
- Long life bearing.
- The chips are thrown into a collection bin.
- Fully made of high-strength metals.
- Robust construction with low center of gravity.
- The position of the engine facilitates its cleaning and maintenance.
- Anti-fouling spray duct design.
- Operation with safety system and emergency button for immediate shutdown.
- EC Conformity.

											
M	€	kg	hp	mm	m³/h	no.	mm	mm	no.	L/h	
KB05		55	Loncin 196cc 6.5 hp	660/570/640	2	2+1	5-15	50	-	0.8	Recoil starter

ACCESSORIES













ACCESSORIES

M	€										
KB10	112	Loncin 196cc 6.5 hp	1750/550/1050	3	2+1	5-15	60-100	2	0.8 L/h	Recoil starter	



EN USAGE AND CHARACTERISTICS

- 4-stroke gasoline engine, with electric starter.
- Semi-automatic feed with slope.
- The anti-vibration clutch minimizes direct movement between the engine and the drum, facilitating cold start and protecting the crank in the event of a cutting system jam.
- Folding funnel to protect and reduce the required space during storage and transport of the machine.
- Ergonomic design and exceptional flexibility thanks to the 2 wheels.
- Drum cutting system with 2 double profile knives plus 1 fixed, high hardening to adjust the cutting thickness.
- Long life bearing.
- Transmission with Kevlar belts.
- The ejection distance is adjusted by the door at the top of the duct.
- Fully made of high-strength metals.
- Robust construction with low center of gravity.
- The position of the engine facilitates its cleaning and maintenance.
- Anti-fouling spray duct design. Easy rotation of the ejection duct 360°.
- Easily accessible impeller without the use of tools.
- Large wheels and towbar.
- Operation with safety system and emergency button for immediate shutdown.
- EC Conformity.

M	€										
		kg	hp	mm	m ³ /h	no.	mm	mm	no.	L/h	
KB15		260	Loncin 420cc 15 hp	1218/2700/1424	7-9	2+1	5-15	100-150	2	1 L/h	Electrical starter









ACCESSORIES

TRACTOR-DRIVEN WOOD CHIPPER KT



EN USAGE AND CHARACTERISTICS

- Semi-automatic feed with slope.
- The hopper can be folded upward with ease for transport and is secured using a cotter pin.
- The chute can be rotated 360 degrees.
- Anti-stuck chute design.
- Door at the top of the chute adjust the launch distance.
- Long life external bearings.
- High hardening impeller (not cast iron) with 4 reversible knives and 1 at the bottom to adjust the cutting thickness, for models **KT10/KT19**.
- Flywheel easy to open.
- Universal 3 points linkage cat. I-II(ø 19.0-22.0mm / 25.0-28.0mm).
- EC Conformity.

M	€								
		kg	hp	mm	mm	m ³ /h	no.	mm	mm
KT10		196	15-50	1380/850/1480	635	7	4+1	5-10	100
KT19		347	30-100	1778/2082/1625	710	13	4+1	5-20	190

ACCESSORIES

T4-80SP

PTO shaft with safety pin 800mm (included)



EN USAGE AND CHARACTERISTICS

- Automatic feed with hydraulic motor-driven roller.
- The hopper can be folded upward with ease for transport and is secured using a cotter pin.
- The chute can be rotated 360 degrees.
- Anti-stuck chute design.
- Door at the top of the chute adjust the launch distance.
- Long life external bearings.
- Flywheel easy to open.
- Is equipped with an autonomous hydraulic system with pump, oil tank and does not require hydraulic pipe connection.
- Manual adjustment valve to regulate the speed of the drive roller.
- Power stop safety device.
- The drum is equipped with 2 high hardening knives and 2 rows of four hammers combining 2 machines (wood chipper - bio chipper) to one.
- Universal 3 points linkage cat. I-II(ø 19.0-22.0mm / 25.0-28.0mm).
- EC Conformity.

M

€



hp

mm

mm

m³/h

no.

mm

mm

KTA10R

225

20-60

2600/1000/1550

346

9

2+8

5-10

100

ACCESSORIES

T4-60SP

PTO shaft with safety pin 600mm (included)

TRACTOR-DRIVEN WOOD CHIPPER **KTR/KTS** hydraulic self feeding



EN USAGE AND CHARACTERISTICS

- Automatic feed with two hydraulic motor-driven rollers.
- The hopper can be folded upward with ease for transport and is secured using a cotter pin.
- The chute can be rotated 360 degrees.
- ww
- Power stop safety device.
- High hardening impeller (not cast iron) with 4 reversible knives and 1 at the bottom to adjust the cutting thickness, for models.
- Door at the top of the chute adjust the launch distance.
- Long life external bearings.
- Double-sided knives can be turned around if required.
- Flywheel easy to open.
- Universal 3 points linkage cat. I-II (ø 19.0-22.0mm / 28.0mm).
- EC Conformity.

M

€



hp

mm

mm

m³/h

no.

mm

mm

KT15S	448	40-80	1270/1320/1879	762	21	4+1	5-15	150	
KT13R	457	30-90	1250/1750/2000	630	19	4+1	5-15	130	
KT16R	695	50-100	1250/2150/2100	720	23	4+1	5-15	160	
KT26R	920	70-120	1420/2750/2650	900	38	4+1	5-15	260	

ACCESSORIES

T5-100SP
T5-80SP
T8-80SP
T8-100SP

PTO shaft with safety pin 1000mm (included)KT15S
PTO shaft with safety pin 800mm (included)KT13R
PTO shaft with safety pin 800mm (included)KT16R
PTO shaft with safety pin 1000mm (included)KT26R