






## EN USAGE AND CHARACTERISTICS

- Independent hydraulic system with oil pump and oil tank.
- Control valve with joystick levers and controls in series.
- Mechanical boom lock for easy and safe transportation.
- Two safety legs, hydraulically independent for maximum stability.
- The main joints are made of high hardening steel.
- Seat with safety belts.
- Boom swivel radius 180 degrees.
- Opening angle of bucket up to 203 degrees.
- Reinforced at all stress points.
- Universal 3 points linkage cat. I-II(ø 19.0-22.0mm / 25.0-28.0mm).
- EC Conformity.



### ACCESSORIES

M	€				A	B	C	D	
		kg	hp	mm	mm	mm	mm	mm	kg
<b>TA250</b>		270	15-45	300	1690	950	2280	2440	312
<b>TA290</b>		540	40-100	300	2420	1950	3170	2900	1350
<b>TA330</b>		700	50-120	400	2550	2250	3450	3300	1700

**TA250**  
**BTAM20** Bucket width 200mm  
**BTAM50** Bucket width 500mm  
**BTAM70** Bucket width 700mm  
**BTAM01** Ripper  
**BTAM02** Thumb

**TA290 / TA300**  
**BTAH20** Bucket width 200mm  
**BTAH50** Bucket width 500mm  
**BTAH70** Bucket width 700mm  
**BTAH90** Bucket width 900mm  
**BTAH01** Ripper  
**BTAH02** Thumb

**T4-60SP**


PTO shaft with safety pin 600mm (included)

# TRACTOR BACKHOE **HADES** with side shift







## EN USAGE AND CHARACTERISTICS

- Independent hydraulic system with oil pump and oil tank.
- Control valve with joystick levers and controls in series.
- Mechanical boom lock for easy and safe transportation.
- Two safety legs, hydraulically independent for maximum stability.
- The main joints are made of high hardening steel.
- Seat with safety belts.
- Boom swivel radius 180 degrees.
- Opening angle of bucket up to 203 degrees.
- Reinforced at all stress points.
- The **TA250 PRO** boom have mechanical move with lock almost 700 mm laterally.
- **TA290 PRO / TA260 PRO / TA330 PRO** models have a 960 mm hydraulic arm displacement.
- Universal 3 points linkage cat. I-II(ø 19.0-22.0mm / 25.0-28.0mm).
- EC Conformity.



### ACCESSORIES

M	€				A	B	C	D	
		kg	hp	mm	mm	mm	mm	mm	kg
<b>TA250 PRO</b>		270	15-45	300	1690	950	2280	2440	312
<b>TA260-PRO</b>		430	30-80	300	1800	1550	2400	2550	950
<b>TA290 PRO</b>		600	40-100	300	2150	1950	3170	2900	1350
<b>TA330 PRO</b>		840	50-120	400	2550	2250	3450	3300	1700

**TA250**  
**BTAM20** Bucket width 200mm  
**BTAM50** Bucket width 500mm  
**BTAM70** Bucket width 700mm  
**BTAM01** Ripper  
**BTAM02** Thumb

**TA290 / TA300**  
**BTAH20** Bucket width 200mm  
**BTAH50** Bucket width 500mm  
**BTAH70** Bucket width 700mm  
**BTAH90** Bucket width 900mm  
**BTAH01** Ripper  
**BTAH02** Thumb

**T4-60SP**

PTO shaft with safety pin 600mm (included)